XWL-800 Series LED WORK LIGHT | 2500 LUMENS







Feature

- Die cast aluminum housing, polycarbonate lens and high impact bezel
- IP68 & IP69K
- Low current draw
- Constant current circuit draw
- 4 beam patterns
- 50,000+ hours LED service life



Benefit

Virtually unbreakable.

Will withstand dust, dirt, sand, and water submersion.

Energy efficient, save on fuel costs.

Light does not dim even if voltage fluctuates.

Delivers 2500 lumens of bright white illumination.

Get light where it's needed most.

Long lasting investment, quality product.







Specifications

Operating Voltage: 12 - 24Vdc
Operating Current: 1.8A @ 12Vdc
0.9A @ 24Vdc

Power Consumption: 22W

Temperature Range: -40°C to +80°C Ingress Protection: IP68 & IP69K Weight: 2.2lbs (1.0kg)

Housing: Die Cast Aluminum Alloy A380 | Black E-Coat

Lens: Automotive Optical Grade

Hard-Coated Polycarbonate

Connection: 6" Wire

Polarity: Reverse Voltage Protected

Vibration Resistance: 10-500Hz @ 5Grms

Mounting: C-Bracket (Powder Coated Steel)

Swivel Bracket (Zinc Dichromate Plating)


EMC Rated: EMC EN 13309: 2010


Part #	Beam Pattern	Lumens	Operating Voltage	
81261/HO	Spot	2500	12 - 24Vdc	
81262/HO	Wide Flood	2500	12 - 24Vdc	
81263/HO	Medium Flood	2500	12 - 24Vdc	
81281/HO	Hybrid	2500	12 - 24Vdc	
Swivel Bracket				
81264/HO	Spot	2500	12 - 24Vdc	
81265/HO	Wide Flood	2500	12 - 24Vdc	
81266/HO	Medium Flood	2500	12 - 24Vdc	
81267/HO	Hybrid	2500	12 - 24Vdc	

Accessories

HW02A Hardware Kit | C-Bracket 98189 Hardware Kit | Swivel Bracket


98195 Easy Grip Handle - Black | Blue | Orange









C-Bracket





Swivel Bracket

Beam Patterns











For more lighting and electronic solutions, please check out our catalogue.